




Aim.70

Product Category: *Downlight*

t: +(44) 020 7139 5129

e: enquiries@lightingoflondon.co

w: www.lightingoflondon.co




The Aim.70 is an elegantly designed downlight that can be used in both dry and humid interiors. Its sleek design, which features a deep black baffle and an ultra-slim aluminum powder-coated bezel, provides low glare and minimal architectural lighting.

The fitting allows for 20° of tilt and 180° of pan, enabling pinpoint accuracy of light. The Aim.70 also has an advanced heat sink that allows for cool running while requiring only 58mm height clearance.

This fitting can accommodate beam angles of 15°, 24°, 36°, or 60°, with Correlated Colour Temperatures (CCT) of 2700K, 3000K, or 4000K.

Material	<i>Aluminium</i>	Beam Angle	<i>15° / 24° / 36° / 60°</i>
Lumen Output	<i>710Lm</i>	Luminous Efficacy	<i>81lm / W</i>
Power	<i>8.75W 36V 250mA</i>	IP Rating	<i>54</i>
Dimmable	<i>Yes</i>	Fire Rating	<i>60min</i>
CRI	<i>>95</i>	Driver Required	<i>Yes</i>
Power Factor	<i>>0.98</i>	Binning	<i>2 - 3 SDCM</i>
Size	<i>68.5mm x 58mm</i>	DALI Control	<i>Yes</i>
Cut Out	<i>62mm</i>	Colour Temperature	<i>2700K / 3000K / 4000K</i>

Dimensions



Lux Distribution Curve

