

Technical Data Sheet

Beam.L


Product Category: Uplights/ Exterior

🟗 +(44) 020 7139 5129 😢 enquiries@lightingoflondon.co 🛛 🗤: www.lightingoflondon.co


The Beam.L is a high-quality lighting fixture that is designed to be versatile and discreet. It is perfect for grazing and up-lighting requirements, making it suitable for a variety of applications both indoors and outdoors. Despite its compact size, it delivers a generous output, making it ideal for residential environments. Additionally, it comes with an installation sleeve for easy setup and features resin-filled cable entry and a gland that provides exceptional protection against water ingress.

Material	Aluminium & Stainless Steel 316	Beam Angle	15°/23°/36°
Lumen Output	495Lm	Luminous Efficacy	75lm / W
Power	6.6W 19V 350mA	IP Rating	67
Dimmable	Yes	Driver Required	Yes
CRI	>95	Binning	2 - 3 SDCM
Power Factor	>0.98	DALI Control	Yes (third party driver required)
Size	Ø65mm x 69mm L	Colour Temperature	2700K / 3000K
Cut Out	54mm		


Light Distribution Curve







Lux Distribution Curve



LIGHTING OF LONDON Worlds End Studios, London, SW10 0RJ https://www.lightingoflondon.co, +(44) 020 7139 5129 @All Rights Reserved