




Profile.60

Product Category: *Downlight*

t: +(44) 020 7139 5129

e: enquiries@lightingoflondon.co

w: www.lightingoflondon.co




The Profile.60 is an elegantly designed downlight that can be used in both dry and humid interiors. Its sleek design, which features a deep black baffle and an ultra-slim aluminum powder-coated bezel, provides low glare and minimal architectural lighting.

The Profile.60 has a superior designed heat sink, allowing for cool running while only requiring 56mm height clearance.

The fitting comes can accommodate a 20° or 36° beam, with Correlated Colour Temperatures (CCT) of 2700K, 3000K, or 4000K.

Material	<i>Aluminium</i>	Beam Angle	<i>20° / 36°</i>
Lumen Output	<i>710Lm</i>	Luminous Efficacy	<i>81lm / W</i>
Power	<i>8.75W 36V 250mA</i>	IP Rating	<i>54</i>
Dimmable	<i>Yes</i>	Fire Rating	<i>60min</i>
CRI	<i>>95</i>	Driver Required	<i>Yes</i>
Power Factor	<i>>0.98</i>	Binning	<i>2 - 3 SDCM</i>
Size	<i>58mm x 56mm</i>	DALI Control	<i>Yes</i>
Cut Out	<i>50mm</i>	Colour Temperature	<i>2700K / 3000K / 4000K</i>

Dimensions



Lux Distribution Curve

