


Technical Data Sheet




The Wave.20 magnetic LED module boasts seamless magnetic connection to the Magtrak profile, ensuring a sleek, modern appearance and effortless installation. This gentle wall-washer LED module emits a stunning 110° beam @ 30° tilt, enriching any surface it illuminates. Whether you prefer TRIAC or DALI, this versatile module can be customised to meet your specific lighting control needs.

Material	Aluminium	Beam Angle	110° @ 30° tilt
Lumen Output	750Lm	Luminous Efficacy	75lm / W
Power	10W 24V	IP Rating	21
Dimmable	Yes	Driver Required	N/A
CRI	>95	Binning	2 - 3 SDCM
Power Factor	>0.98	DALI Control	Yes
Size	193mm	Colour Temperature	2700K / 3000K / 4000K
Cut Out	N/A		

Light Distribution Curve



Dimensions



Lux Distribution Curve

3.28ft	10.220 fc	Д	37.530 fc	2.69ft
1.0m	110.00 lx	\mathcal{A}	403.90 lx	0.82m
6.56ft	2.554 fc		9.381 fc	5.39ft
2.0m	27.50 lx		101.00 lx	1.64m
9.84ft	1.135 fc		4.169 fc	8.08ft
3.0m	12.22 lx		44.88 lx	2.46m
13.12ft	0.639 fc		2.345 fc	10.78ft
4.0m	6.87 lx		25.24 lx	3.28m
16.40ft	0.409 fc		1.501 fc	13.47ft
5m	4.40 lx	7	16.16 lx	4.11m
Height	Avg E	Angle 44.65°	Max E	Diam.