## **Technical Data Sheet**

## Follow.Me.R

SKU: Follow.Me.R

**t:** +(44) 020 7139 5129

enquiries@lightingoflondon.co

www.lightingoflondon.co




The Follow.Me.R recessed spotlight is highly versatile, offering almost complete directional control to the user. It comes with an adjustable cylindrical fitting that can point in a 355° horizontal range. If a 90° vertical spotlight is needed, it can be recessed back into its fitting to sit flush with the ceiling. The Follow.Me.R is designed to blend seamlessly into its surroundings.

This spotlight comes with three beam angle options- a sharp 15°, a generous 24° or a wider 36°, giving you ample options to highlight any wall or object with a warm 2700k glow.

**Product Categories:** Spotlights / Downlights

Material	Aluminium	Beam Angle	15°/24°/36°
Lumen Output	600Lm	Luminous Efficacy	75lm / W
Power	8W 36V 180mA	IP Rating	21
Dimmable	Yes	Driver Required	TRIAC dimmable driver supplied
CRI	>95	Binning	2 - 3 SDCM
Power Factor	>0.98	DALI Control	Yes (third party driver required)
Size	30mm x 65mm L	Colour Temperature	2700K / 3000K / 4000K
Cut Out	50mm	Fire Rating	60 min

## **Dimensions**



350°

## **Lux Distribution Curve**



		24°		
3.28ft	Emax	/ \	E(Ix)	1.41
1.0m	2.450 lx	1	1.721 lx	0.43
6.56ft				2.85
2.0m	612 lx		430 lx	0.87
9.84ft				4.10
3.0m	271 lx		191 lx	1.25
13.12ft				5.71
4.0m	152 lx		107 lx	1.74
Height	Max E	Beam angle 24°	Ave E	Diamete

